

# COMPWISE®

## RUGGED SOLUTIONS

### RUGGED-770 (SPECS)

<b>CPU</b>	<ul style="list-style-type: none"> <li>• Intel Pentium M Processor 1.4GHz</li> <li>• Optional 1.6GHz</li> </ul>
<b>Core logic</b>	<ul style="list-style-type: none"> <li>• Intel 855GM + ICH4</li> </ul>
<b>L2 Cache</b>	<ul style="list-style-type: none"> <li>• On-die 1MB L2 Cache</li> </ul>
<b>System BIOS</b>	<ul style="list-style-type: none"> <li>• 512KB Flash EEPROM</li> <li>• ACPI 2.0 capability</li> <li>• PC2001 compliance</li> </ul>
<b>Memory</b>	<ul style="list-style-type: none"> <li>• Two 200-pin PC2100 DDR SODIMM socket for memory expansion</li> <li>• Standard 256MB; Max. : 1GB</li> </ul>
<b>VGA Controller</b>	<ul style="list-style-type: none"> <li>• Integrated 32-bit 3D/2D gfx core with Dynamic Video Memory Technology</li> <li>• Duel View function</li> <li>• LCD/CRT simultaneous display capability</li> </ul>
<b>Video Memory</b>	<ul style="list-style-type: none"> <li>• Shared system memory 64MB</li> </ul>
<b>Bay 1 Modules &amp; Functions</b>	<ul style="list-style-type: none"> <li>• Standard FDD swappable for optional CD-ROM, DVD/CD-RW Combo, Bay 1 Battery, 2nd HDD and DVD-ROM</li> <li>• Integrated with Type III× 1 or Type II × 2 PCMCIA Card Slot,</li> <li>• ExCA / ZV / CardBus compatible</li> <li>• Integrated IEEE 1394 Port</li> <li>• Integrated 16 Bit PCI Audio</li> </ul>
<b>HDD</b>	<ul style="list-style-type: none"> <li>• Inter-changeable module, Support Ultra DMA</li> <li>• 2.5" 9.5mm height, Shock mounted</li> <li>• Standard: 20GB; Optional: 40GB/60GB/80GB</li> </ul>

<b>Display</b>	<ul style="list-style-type: none"> <li>• 12.1" TFT, XGA LCD resolution: 1024x768 (Standard)</li> <li>• 14.1" TFT, XGA LCD resolution: 1024x768 (Optional)</li> <li>• Optional 12.1" Touch Screen</li> <li>• Optional Sun-light Readable LCD</li> </ul>
<b>Keyboard</b>	<ul style="list-style-type: none"> <li>• Water-proof and dust-proof rubber Keyboard</li> <li>• LED Back-Light Rubber Keyboard (Optional)</li> </ul>
<b>Pointing Device</b>	<ul style="list-style-type: none"> <li>• Water-proof and dust-proof touch pad</li> <li>• Enhance pressure sensitive Glove-Use Touch Pad (Optional)</li> </ul>
<b>PCMCIA/CardBus</b>	<ul style="list-style-type: none"> <li>• Bay 1 Type III× 1 or Type II × 2</li> <li>• ExCA compatible - ZV/CardBus support</li> </ul>
<b>I/O Port</b>	<ul style="list-style-type: none"> <li>• Serial port× 1,</li> <li>• Parallel port (EPP/ECP)× 1</li> <li>• RJ-11 x 1</li> <li>• RJ-45 x 1</li> <li>• VGA monitor port × 1</li> <li>• USB 2.0 x 1</li> <li>• DC input x1</li> <li>• IrDA × 1(4Mbps and 115Kbps)</li> <li>• Port Replicator × 1</li> <li>• IEEE 1394 Port × 1 ( Integrated in Bay1 )</li> <li>• PCI Audio support external Audio Jack Cable for Mic-In and Line-Out Ports</li> </ul>
<b>Battery</b>	<ul style="list-style-type: none"> <li>• Li-Ion Primary Smart Battery for 5 hours</li> <li>• Bay1 Li-Ion Smart Battery(Optional)</li> <li>• Bay2 Li-Ion Smart Battery(Optional)</li> </ul>
<b>AC adapter</b>	<ul style="list-style-type: none"> <li>• Universal AC adapter</li> <li>• Input:100-240v, 50/60Hz AC</li> </ul>
<b>Dimensions</b>	<ul style="list-style-type: none"> <li>• 310(W)x255(D)x70(H) mm ; 12.2" x 10" x 28"</li> </ul>
<b>Weight</b>	<ul style="list-style-type: none"> <li>• 14.3 lbs(6.5 Kg)</li> </ul>
<b>Software</b>	<ul style="list-style-type: none"> <li>• Support Windows Windows 2000 /Windows XP</li> </ul>