

COMPWISE®

RUGGED SOLUTIONS

RUGGED-130 (SPECS)

CPU	<ul style="list-style-type: none"> • Intel Pentium M Processor LV 1.1GHz in μ-FCBGA package • FSB 400MHz
Core logic	<ul style="list-style-type: none"> • Intel 855GM Chipset + ICH4-M
L2 Cache	<ul style="list-style-type: none"> • On-die 1MB L2 Cache
System BIOS	<ul style="list-style-type: none"> • 256KB Flash EEPROM • Includes System BIOS, VGA BIOS, plug & play, and ACPI 1.1b capability • Boot from IDE devices and LAN, USB CD-ROM • Suspend to DRAM / HDD • PC2001 compliance
Memory	<ul style="list-style-type: none"> • One 200-pin PC2100 DDR SODIMM socket for memory expansion • Standard: 256MB Max: 1GB
VGA	<ul style="list-style-type: none"> • Integrated graphic controller with 64MB shared system memory
Display	<ul style="list-style-type: none"> • 12.1" TFT XGA (1024x768) LCD • 12.1" touch screen (Optional) • Sunlight Readable Panel (Optional)
Video Memory	<ul style="list-style-type: none"> • Share system memory 64MB
HDD	<ul style="list-style-type: none"> • Standard: 40GB, Integrated, support Ultra DMA-33/66/100 with damper protect. Upgradeable to 60GB • HDD heater for low temp. -4°F./-20°C to 131°F/55°C (Optional)
Optical Drives	<ul style="list-style-type: none"> • CD-ROM (built into the Docking Station) • DVD-ROM, CD R/W (Optional in the Docking Station)
FDD	<ul style="list-style-type: none"> • Included in Docking Station

Keyboard	<ul style="list-style-type: none"> • Water-proof membrane keyboard • Rubber keyboard with back-light (Optional)
Pointing Device	<ul style="list-style-type: none"> • A touch-sensitive control pad with Microsoft Win Mouse function coexist
PCMCIA	<ul style="list-style-type: none"> • Type II x 1 - Card Bus support
Communication	<ul style="list-style-type: none"> • 10/100 Base-T LAN • 56K, V90. Modem • 802.11b Wireless LAN • (Supports Intel PRO/Wireless 2100 LAN mini-PCI type 3B adapter and Intel PROset software) • Wireless Modem (DataTAC or GPRS/GSM or CDMA)
Audio	<ul style="list-style-type: none"> • AC97 audio support • MS-Sound compatible • Built-in one speaker (Mono) • Microphone-in • Line-out
I/O Port	<ul style="list-style-type: none"> • Serial port x 1 • VGA port x 1 • USB 2.0 port x 3 • DC input x1 • Docking Port x1 • RJ-11x1 for 56Kbps Software Modem port • RJ-45 100 Base-T LAN port • Microphone-in & Earphone out ports
Battery	<ul style="list-style-type: none"> • Support 9 cells Li-Ion Battery, up to 3.5 hours battery life
AC adapter	<ul style="list-style-type: none"> • Universal AC adapter • Input: 100-240v, 50/60Hz AC
Dimensions	<ul style="list-style-type: none"> • 10.8" x 9.4" x 1.7" / 276mm x 239mm x 43mm
Weight	<ul style="list-style-type: none"> • 5.94lbs (2.7kg)
Software	<ul style="list-style-type: none"> • Support Windows 2000 / Windows XP