

COMPWISE®

RUGGED SOLUTIONS

RUGGED-27 (SPECS)

Processor	Intel® Pentium® M Processor 1.1/1.3 GHz
Cache	256KB /128KB on die (depends on processor type)
BIOS	Systemsoft flash BIOS
Memory	3.3V Sync Double Data Rate (DDR) DRAM, one 144 pins SO-DIMM for expansion SDRAM module, upgradeable to 512MB;
VGA	32-bit PCI bus, 4MB video memory; Support Dual-View function; LCD/CRT simultaneous display capability
Storage	2.5" HDD with shock resistance damper; 3.5" 1.44MB FDD, external; 5.25", 12.7mm, CD-ROM/ DVD-ROM module, external;
Display	Touch / Pen Input Screen; 10.4" TFT XGA (1024x 768) LCD; Daylight Readable Panel (optional);
Panel	Ctrl Power On/off; Audio Volume Control; Brightness Control; Function keys (F1, F2, F3);
Keyboard	Wireless Keyboard with pointing device (optional)
PCMCIA	One Type-II, ZV/CardBus support
I/O Port	One RS-232 serial port; One USB port; One Docking Port; One IR Port , Complies with IrDA (FIR and SIR); One RJ-11 Modem Port. One wireless K/B IR port One CCD USB port
Port Replicator	Serial x 2; PS/2 x 2; Parallel Port x 1; USB x 2.

	VGA x 1; Ear Phone out x 1; MIC in x 1; DC input x 1; Docking port x 1; External Drive Kit port x 1.
X-Bay	Multiple-choice Wireless solution (LAN, CDPD, GSM); Serial x 2 + IEEE 1394 x 1 port + LAN x1 port; 2nd Flash Disk
External Drives	1.44MB FDD module, USB interface; 24X CD-ROM module, docking port interface; 8X DVD-ROM module, docking port interface.